

BID # 20140729
ELLIS MIDDLE LOCKERS

SPECIFIC INFORMATION

Cross frame members of 16 gauge channel shapes including intermediate cross frame on double and triple tier lockers shall be securely welded to vertical framing members to ensure rigidity.

- Body: Bolt spacing in locker body construction not to exceed 9" o.c. All locker body components shall be made of cold rolled steel specially formed for added strength and rigidity and to ensure tight joints at fastening points. Tops and bottoms shall be 24 gauge with three sides formed 90° and the front offset formed to be flush with the horizontal frame member. Shelves shall be 24 gauge with four sides formed to 90°, the front edge shall have a second bend. Backs and sides shall be 24 gauge.
- Doors: Doors 30" or higher shall be formed from one piece 16 gauge cold rolled sheet steel. Doors less than 12" wide shall be minimum of 18 gauge. Formations shall consist of a full channel shape on the lock side of adequate depth to fully conceal the lock bar, channel formation on the hinge side, and right angle formations across the top and bottom. Doors over 15" wide x 60" & 72" high shall have a 3" wide 20 gauge full height reinforcing pan welded to the inside face of the door on 6" centers.
- Door Handle: 1 & 2 Tier; Handle to consist of zinc alloy die cast case and handle. 40,000 psi maximum tensile strength, chrome plated. Handle to be pulled out to move up latch bar and open door in one motion. Padlock eye for use with 9/32" diameter padlock shackle to be an integral part of handle and to be so located that extension of handle forms a padlock strike. Attachment to latch bar shall be tamper proof and concealed inside the door. The case shall be kick proof type, shielding the movable part and provide a padlock strike to prevent scratching and marring the door. A lock hole cover plate shall be provided for use with padlocks.
- Door Latching: 1 & 2 Tier; Doors to have latch clip engaging the door frame at three points on doors over 42" high and two points on all other doors. Locking device to be positive, automatic type, whereby lock door may be locked when open, then closed without unlocking. One rubber silencer shall be firmly secured in the frame at each heavy gauge latch hook. Latch clips shall be glass filled nylon for long life *

Invitation to Bid
ELLIS MIDDLE LOCKERS

Responses to an Invitation to Bid will be received by the Purchasing Supervisor, Sumner County Board of Education, 1500 Airport Road, Gallatin, TN 37066 for ELLIS MIDDLE LOCKERS until 9:00 a.m. CDT Tuesday, July 29, 2014. Bid responses will be opened at that time, taken under advisement and evaluated. Should you have any questions please contact Darren Frank, Ellis Middle Principal @ darren.frank@sumnerschools.org. All proposals are subject to the Board of Education's conditions and specifications which are available from Vicky Currey, Purchasing Supervisor (615) 451-6560. All bids can be viewed on line at www.sumnerschools.org.

NOTICE TO RESPONDENTS